

The Broadcom® BCM957414A4142CC is a dual-port 25 Gb/s, PCI-Express Gen3 x8 Network Interface Card that supports both SFP28/SFP+ optical modules and copper-direct attach cable.

Compatible with both 62.5um and 50um LC cables; Supports OM1/OM2/OM3/OM4 fiber cables. Protected by high-quality zinc metallic casing to ensure good heat dissipation and low ...

This module is designed to operate over singlemode fiber systems using a nominal wavelength of 1310nm. The electrical interface uses a 20 contact edge type connector. The optical interface uses ...

The SFP28 25G is a single-rate module with an operating range of 0.5m to 70m/100m over OM3/OM4 MMF (Table 1), respectively, compliant with IEEE802.3by 25GBASE-SR optical specs.

Yes, Arista 25G SFP ports allow the flexibility to run multiple speeds and support a full range of 10G SFP+ optical modules.

SFP28 transceiver that supports 25G connections up to 100 m using multi-mode ...

The Cisco 10/25GBASE-LR Module supports a link length of 10 kilometers on standard Single-Mode Fiber (SMF) G.652 at both 10G and 25G. This module requires RS-FEC on the host ...

Enhance the networking infrastructure with this MSA-compatible 25GBASE-LR optical transceiver, ensuring reliable performance and seamless connectivity at distances of up to 10km.

This module is designed to operate over multimode fiber systems using a nominal wavelength of 850nm. The electrical interface uses a 20 contact edge type connector. The optical interface uses duplex LC ...

SFP28 transceiver that supports 25G connections up to 100 m using multi-mode fiber with a duplex LC UPC connector.

Discover the advantages, specifications, and applications of 25G optical transceiver solutions--for high-speed data center, enterprise, and telecom networks.

Web: <https://csc-energia.com.pl>